

# SOLSPERSE™ 67000

A 100% active polymeric compatibiliser

PERFORMANCE COATINGS

## PRODUCT DESCRIPTION

SOLSPERSE 67000 is a 100% active polymeric compatibiliser, which will extend acceptance of universal colorants and tint pastes.

## FEATURES/BENEFITS

In the applications below, the following benefits are achieved:

- Compatibility with a wide range of decorative binders
- Effectively dissipates waterborne colorants in solvent based paints (including silicate paints)
- Improve colour acceptance
- Reduce flooding, floating and improved flocculation resistance
- Suitable for APE & VOC free colourants

## PHYSICAL CHARACTERISTICS\*

Appearance	Dark brown viscous liquid
Flash point (°C)	TBD
Density (g/cm <sup>3</sup> )	0.90
Gardner Colour	20 max

\* Property values represent typical results only and are not to be considered specifications.

## TYPICAL APPLICATIONS

- Decorative alkyd paints (medium / high solids)
- Styrene acrylic paints

Post Additive: Mix SOLSPERSE 67000 with the alkyd base paint using mechanical mixing, prior to addition of the universal colourant. Addition levels of 0.5 to 5% w/w can be used, based on total formulation.

Universal colorants and tint pastes:

SOLSPERSE 67000 can be added to the grind stage in combination with a co-dispersant (I.E. SOLSPERSE 27000) to produce a universal colorants compatible with a range of decorative binders. A ladder series on the dosage level to be undertaken to establish the optimum loading.

## RECOMMENDED RETEST DATE (RRD)/STORAGE

SOLSPERSE 67000 is packed in 20 Kg and 200 Kg plastic drums.

Shelf life: 2 years

For storage, please refer to the MSDS.

## REGULATORY STATUS

Please see the product's current material safety data sheet, MSDS, for regulatory information. You can request an MSDS at [www.lubrizolcoatings.com](http://www.lubrizolcoatings.com).

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

Trademarks owned by The Lubrizol Corporation © The Lubrizol Corporation 2012, All Rights Reserved. on hold Blackley 4/11/14



[www.lubrizolcoatings.com](http://www.lubrizolcoatings.com)